



HD 6/13 CX Plus

Compact, high performance pressure washer with unique stand-up or lay-flat operating positon, large carry handle and built-in hose reel.









1 Mobility

- The integrated carrying handle on the front of the machine enableseasy loading and convenient transport.
- Push handle can be retracted at the push of a button.

2 Flexibility

- Vertical and horizontal operation possible.
- The wheels are not on in horizontal operation. In this way, the machine offers maximum stability.





3 Accessory storage


- Screw connections (M 18 × 1.5) for storing surface cleaner directlyon the machine.
- Practical nozzle compartments for triple nozzle and rotary nozzle.

4 Quality

- The automatic pressure relief protects the components and extends the service life.
- High-quality brass cylinder head.

TECHNICAL DATA AND EQUIPMENT.

KARCHER



HD 6/13 CX Plus

Save energy and time: EASY!Force high-pressure guns and EASY!Lock quick-release locks.

| Technical data | | |
|--|-------------|---|
| Order No. | | 1.520-163.0 |
| EAN code | | 4039784945456 |
| Current type | Ph / V / Hz | 1 / 230 / 50 |
| Flow rate | l/h | 590 |
| Operating pressure | bar / MPa | 130 / 13 |
| Max. pressure | bar / MPa | 190 / 19 |
| Max. water feed temperature | °C | 60 |
| Power rating | kW | 2,9 |
| Weight | kg | 27,5 |
| Dimensions (L x W x H) | mm | 380 × 370 × 930 |
| | | |
| | | |
| Equipment | | |
| Equipment Trigger gun | | Easy-press trigger gun |
| Trigger gun Trigger gun with soft grip | | Easy-press trigger gun |
| Trigger gun | m | |
| Trigger gun Trigger gun with soft grip | m mm | 8 |
| Trigger gun Trigger gun with soft grip High-pressure hose | | ■ 15 / ID 6, 250 bar |
| Trigger gun Trigger gun with soft grip High-pressure hose Spray lance | | 15 / ID 6, 250 bar 850 |
| Trigger gun Trigger gun with soft grip High-pressure hose Spray lance Triple nozzle (0°/25°/40°) | | 15 / ID 6, 250 bar 850 Manual |
| Trigger gun Trigger gun with soft grip High-pressure hose Spray lance Triple nozzle (0°/25°/40°) Dirt Blaster spray lance Integral high-pressure hose reel Anti-twist system (AVS) | | 15 / ID 6, 250 bar 850 Manual |
| Trigger gun Trigger gun with soft grip High-pressure hose Spray lance Triple nozzle (0°/25°/40°) Dirt Blaster spray lance Integral high-pressure hose reel Anti-twist system (AVS) Pressure switch control | | 15 / ID 6, 250 bar 850 Manual |
| Trigger gun Trigger gun with soft grip High-pressure hose Spray lance Triple nozzle (0°/25°/40°) Dirt Blaster spray lance Integral high-pressure hose reel Anti-twist system (AVS) | | 15 / ID 6, 250 bar 850 Manual |

KARCHER

٦

ACCESSORIES FOR HD 6/13 CX PLUS 1.520-163.0







| | | Order No. | ID | Max. working pressure | Length | Р | rice | Description | |
|---|---------|------------------|------|--------------------------|---------|---|------|---|--|
| Standard with unions on both sides | ; | I | | | | | | | |
| High-pressure hose packaged | 1 | 6.391-342.0 | ID 8 | 315 bar | 10 m | | | | |
| High-pressure hose, 30 m DN 8, including rotary coupling | 2 | 6.390-293.0 | ID 8 | 315 bar | 30 m | | | With rotary coupling, 2 x M 22 x 1.5 | |
| Longlife 400 with unions on both s | ides | | | | · · · · | | | | |
| High pressure hose DN 6, 10 m, drehbar,l | 3 | 6.391-883.0 | ID 6 | 400 bar | 10 m | | | With rotary coupling, 2 x M 22 x 1,5 | |
| High-pressure hose packaged | 4 | 6.391-354.0 | ID 8 | 400 bar | 10 m | | | | |
| High-pressure hose Longlife 400, 15 m, DN 8, including rotary coup- ling | 5 | 6.389-709.0 | ID 8 | 400 bar | 15 m | | | With rotary coupling, 2 x M 22 x 1.5 | |
| High-pressure hose Longlife 400, 30 m DN 8, including rotary coup- ling | 6 | 6.390-294.0 | ID 8 | 400 bar | 30 m | | | | |
| High-pressure hose 1.5 m, DN 8, including connectors | 7 | 6.390-178.0 | ID 8 | 400 bar | 1,5 m | | | 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink pro- tection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5). | |
| Longlife food industry version with | n unior | ns on both sides | | | | | | | |
| High pressure hose food DN 8 / 10 _m | 8 | 6.391-864.0 | ID 8 | 400 bar | 10 m | | | Longlife HP hose for use in the food industry. Außende- cke## animal-grease-resistant, non-colour-bleeding materi- | |
| High-pressure hose food industry 400 bar, 20 m, DN 8, including rotary coupling | 9 | 6.391-887.0 | ID 8 | 400 bar | 20 m | | | al. With rotary coupling, 2 x M 22 x 1,5 | |
| Standard with push-in nipple on bo | th sid | es | | | | | | | |
| High-pressure hose DN 6, 15m for hose reel | 10 | 6.391-417.0 | ID 6 | 250 bar | 15 m | | | 15 m high-pressure hose with patented (rotating) AVS trig- ger gun connector and nipple connector for hose reel. | |
| Standard | | | | · | | 1 | | | |
| High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connec- tion | 11 | 6.391-875.0 | ID 6 | 300 bar | 10 m | | | With patented AVS connection in the trigger gun (pivot- mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar | |
| Longlife 400 | | | | | | | | | |
| High pressure hose DN 6, 10 m, Longlife | 12 | 6.391-882.0 | ID 6 | 400 bar | 10 m | | | With patented AVS connection in the trigger gun (pivot- mounted). | |
| High-pressure hose packaged | 13 | 6.391-351.0 | ID 8 | 400 bar | 10 m | | | | |
| ligh-pressure hose packaged | 13 | 6.391-351.0 | ID 8 | 400 bar | 10 m | | | | |




| | | Order No. | Flow rate | | Price | Description | |
|--|-------|-----------------|---------------------|-------------|-----------|---|--|
| Easy Press high-pressure gun with h | oldin | g power reducti | on (Kärcher patent) | | | | |
| Easy press high-pressure trigger gun with softgrip | 1 | 4.775-463.0 | | | | Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter. | |
| Trigger guns | | | | | | | |
| High end high-pressure trigger gun | 2 | 4.775-823.0 | | | | | |
| Quick connect | | | | · · · · | | • • | |
| Quick coupling | 3 | 6.401-458.0 | | | | For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female. | |
| Plug nipple | 4 | 6.401-459.0 | | | | Hardened stainless steel nipple for quick coupling 6.401- 458. With M22 x 1,5 male. | |



| | | Order No. | Max. working pressure | Nozzle size | | Price | Description |
|---------------------|---|-------------|--------------------------|-------------|--|-------|---|
| Triple nozzles | | | | | | | |
| Triple nozzle 038 | 1 | 4.767-149.0 | 300 bar | 38 | | | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5. |
| Dirt Blaster, small | | | | | | | |
| Dirt blaster | 2 | 4.767-023.0 | 180 bar | 40 | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 180 bar, 18 MPa, 60°C. |
| | 3 | 4.767-231.0 | 180 bar | 40 | | | |
| Dirt blaster, large | | | | | | | |
| Dirt blaster 04 | 4 | 4.763-252.0 | 300 bar | 40 | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. |

 \blacksquare Included in delivery. $\hfill\square$ Available accessories. $\hfill\blacksquare$ Extension hose.



| | | Order No. | Max. working | Length | | Price | Description |
|---|---|-------------|--------------|--------|--|-------|---|
| Rotating spray lances | | | • • • • • | | | | |
| Lance 850 mm, rotatable, ergono- mic | 1 | 4.760-663.0 | 300 bar | 840 mm | | | 850 mm stainless steel lance (manual coupling) with ergono- mic handle for ease of use and protection. Rotatable 360° under pressure. |
| Spray lance | | | | | | | |
| Lance 250 mm, non-rotatable | 2 | 4.760-667.0 | | 250 mm | | | 250 mm stainless steel lance. With manual coupling. Non- rotatable. |
| Double lance | | | | | | | |
| Double lance 960 mm | 3 | 6.394-665.0 | 310 bar | 960 mm | | | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning). |
| Angular spray lance | | | · | | | | |
| WC and gutter lance | 4 | 4.760-073.0 | | | | | Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets. |
| Gutter cleaner | | | | | | | |
| Gutter cleaning lance | 5 | 2.642-305.0 | | | | | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. |
| Undercarriage spray lance | | | | | | | |
| Underbody lance | 6 | 4.760-245.0 | | 700 mm | | | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. |

luded in delivery. Available accessories.

Extension ho



| | | | | | Diame- | | |
|--|----------|-------------|-------------|-------------|-------------|-------|---|
| | | Order No. | Flow rate | Nozzle size | ter | Price | Description |
| Hard surface cleaner FR Classic | | | | | | | |
| | 1 | 2.643-476.0 | | | | | |
| Hard surface cleaner FR 30 | | | | | | | |
| FR 30 | 2 | 2.642-997.0 | | | 300 mm | | |
| Hard surface cleaner FR 30 ME | | | | | | | |
| FR 30 ME surface cleaner | 3 | 2.640-355.0 | | | 300 mm | | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry. |
| Machine-specific nozzle kit for FR | | | | | · · · · · · | | |
| Nozzle kit for surface cleaners (type-specific) 450 - 500 l/h | 4 | 2.640-482.0 | 450-500 l/h | | | | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h). |
| Machine-specific nozzle kits for F | R Classi | c | | | | | |
| | 5 | 2.885-312.0 | | 40 | | | |



| | | Order No. | Nozzle size | | Price | Description | |
|---------------------------------------|---|-------------|-------------|--|-------|--|--|
| HP nozzle spray angle 0° | | | | | | | |
| High-pressure nozzle spray angle °0 | 1 | 2.884-533.0 | 40 | | | High-pressure nozzle with powerful jet for extremely stub- | |
| Power nozzle spray angle 15° | | | | | | | |
| Power nozzle spray angle 15° | 2 | 2.883-388.0 | 40 | | | Fan jet nozzle with 15° spray angle suitable for stubborn dirt. $\hfill \begin{tabular}{ll} \label{eq:first} \end{tabular}$ | |
| Power nozzle spray angle 25° | | | | | | | |
| Power nozzle spray angle 25° | 3 | 2.883-805.0 | 38 | | | Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains. $\left[\right.$ | |
| | 4 | 2.884-521.0 | 250 | | | | |
| Power nozzle spray angle 40° | | | | | | | |
| Power nozzle spray angle 40° | 5 | 2.884-522.0 | 40 | | | Power nozzle with a 40° spray angle and fan jet, suitable for $[large areas and sensitive surfaces. \end{tabular} \label{eq:large}$ | |

KARCHER



| | | Order No. | | | Price | Description | |
|--|--------|-------------|---|---|-------|--|--|
| Coupling parts | | | I | 1 | | 1 | |
| | 1 | 6.987-705.0 | | | | | |
| Coupling | | | | | | | |
| Coupler -2xM22x1,5 | 2 | 4.403-002.0 | | | | Brass double connector for connecting and extending high- pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m. | |
| Connector | | | | | | | |
| Nozzle connector/screw connector | 3 | 4.402-022.0 | | | | Nozzle connector/screw connector for connecting high- pressure nozzles and accessories to the high-pressure trig- ger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5. | |
| Adapter | | | | | | | |
| Adapter M22 - Swivel | 4 | 4.424-004.0 | | | | M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connec- tion. | |
| HP detergent injector | | | | | | | |
| Detergent injector for high pressu- re | 5 | 3.637-170.0 | | | | Cleaning agent dosage at high pressure 3 - 5 % | |
| Machine-specific nozzle kit with ord | ler no | . 3.637-170 | | | | | |
| Machine-specific nozzle kit with order no. 3.637-170.0 HD 500- 700 l/h | 6 | 4.769-045.0 | | | | For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union | |

HD 6/13 CX Plus, 1.520-163.0, 2016-10-07



| | | Order No. | Nozzle size | | Price | Description |
|---|--------|-------------|-------------|--|-------|---|
| Wet blasting attachment (without n | ozzle) | | | | | |
| Wet blasting attachment with flow control (without nozzles) | 1 | 4.762-010.0 | | | | Paint, rust and scale removal made easy: Kärcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. |
| Wet blasting attachment without flow control (nozzles not included) | 2 | 4.762-022.0 | | | | Paint, rust and scale removal made easy: Kārcher wet blas- ting attachment with flow control for adding blasting abrasi- ve to the high-pressure jet. Without flow control. |
| Nozzle pack for wet blasting attach | ment | | | | | |
| Nozzle kit for wet blasting attach- ment 035 | 3 | 2.638-526.0 | 35 | | | Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment per- formance. Only in combination with wet blasting attachment 4.762-010/-022. |
| Boron carbide nozzle | | | | | | |
| Boron carbide nozzle, for machi- nes as of 1000 l/h | 4 | 6.415-084.0 | 6 mm | | | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation. |



| | | Order No. | Max. working pressure | Nozzle size | Diame- ter | Price | Description | |
|---|---|-------------|--------------------------|-------------|---------------|-------|---|-----|
| Pipe cleaning hose, ID 6 | | | | | | | | |
| Pipe cleaning hose | 1 | 6.390-028.0 | 120 bar | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | |
| Pipe cleaning hose, DN 6, 30 m | 2 | 6.390-029.0 | 120 bar | | | | 30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle). | |
| Pipe cleaning hose, DN 6, 20 m, 220 bar | 3 | 6.390-030.0 | 250 bar | | | | 20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle). | |
| Pipe cleaning nozzle | | | | | | | | |
| Drain cleaning dirt blaster D 25/040 | 4 | 6.415-944.0 | | 40 | 25 mm | | The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the | |
| Drain cleaning dirt blaster D 30/040 | 5 | 6.415-946.0 | | 40 | 30 mm | | necessary forward movement, as well as convenient hand- ling. | |
| Drain cleaning dirt blaster D 35/040 | 6 | 6.415-948.0 | | 40 | 35 mm | | | |
| Pipe cleaning nozzle | 7 | 5.763-015.0 | | 55 | 16 mm | | 16 mm pipe cleaning nozzle with internal thread. Various je | t 🗆 |
| | 8 | 5.763-016.0 | | 60 | 16 mm | | directions for environmentally-friendly cleaning of blocked drains and pipes. | |
| | 9 | 5.763-017.0 | | 50 | 30 mm | | 30 mm pipe cleaning nozzle with internal thread. Various je directions for environmentally-friendly cleaning of blocked drains and pipes. | t |



| | | Order No. | Flow rate | | Price | Description |
|--------------------------|---|-------------|-----------|--|-------|--|
| Cup foam lance | | | | | | |
| Foam lance nozzle Ø1,5 | 1 | 6.394-969.0 | | | | |
| Foam nozzle mounting kit | | | | | | |
| Foam nozzle kit | 2 | 2.637-926.0 | | | | Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica- tion times are necessary. |



| | | Order No. | Length | | Price | Description | |
|--|---|-------------|--------|--|-------|---|--|
| Automatic, self-winding hose reels | | | | | | | |
| Swivel holder | 1 | 2.639-931.0 | | | | Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. [Rotatable 120°. Galvanised steel. | |
| Add-on kit hose reel plastics | 2 | 6.392-975.0 | 20 m | | | Automatic hose reel for 20 m high-pressure hose. The con- sole is made from powder-coated steel, the drum is made from plastic. | |
| Add-on kit hose reel | 3 | 6.392-965.0 | 20 m | | | Automatic hose reel for 20 m high-pressure hose. The con- sole consists of stainless steel, the drum is made from plas- tic. | |
| Hose reel, automatic, 20 m, pain- ted | 4 | 2.639-919.0 | 20 m | | | Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose. | |
| Hose reel, automatic, 20 m, stain- less steel | 5 | 6.391-421.0 | 20 m | | | Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose. | |

KARCHER



| | | Order No. | Length | Diameter | | Price | Description | |
|--|---|-------------|--------|----------|---|-------|---|---|
| Starting current limiter | | | 1 | | 1 | | I | |
| Starting current limiter | 1 | 2.637-495.0 | | | | | Reduces starting current in single-phase supply and protects line fuse. | C |
| Geka coupling | | | | | | | | |
| With hose nozzle, R 1/2" | 2 | 6.388-461.0 | | | | | with hose liner | E |
| With hose nozzle, R 3/4" | 3 | 6.388-455.0 | | | | | | E |
| With female thread, R 3/4" | 4 | 6.388-473.0 | | | | | with female thread | |
| Suction filter | | | | | | | | |
| Suction filter with check valve | 5 | 4.730-012.0 | | | | | Brass suction filter suitable for ponds, storage tanks, etc. With check valve. | |
| Fine-mesh water filter | | | | | | | | |
| Fine-mesh water filter with adap- ter | 6 | 4.730-102.0 | | | | | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contai- ned in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1". | |
| Water supply hose | | | | | | | | |
| Water supply hose | 7 | 4.440-038.0 | 7,5 m | | | | NW 13 R1" / R 3/4", up to 30 °C | E |
| | 8 | 4.440-207.0 | 7,5 m | | | | NW 19 R1" / R 3/4", up to 85 °C, for pick-up | E |
| Backflow check valve | | | | | | | | |
| Backflow preventer | 9 | 2.641-374.0 | | | | | To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection | |



| | | Order No. | Flow rate | | | | Price | Description | | | |
|------------------------|---|-------------|-------------|-------------------|--|--|-------|--|--|--|--|
| Push-on washing brush | | | | | | | | | | | |
| Push-on washing brush | 1 | 4.762-497.0 | | | | | | With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles. | | | |
| Rotating washing brush | | | | | | | | | | | |
| | 2 | 4.762-560.0 | 500-800 l/h | | | | | | | | |
| | 3 | 4.762-561.0 | 500-800 l/h | | | | | | | | |
| Included in delivery. | I Included in delivery. Available accessories. | | | ▲ Extension hose. | | | | | | | |