

SAFETY DATA SHEET FINE FABRIC SOLVENT CLEANER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name FINE FABRIC SOLVENT CLEANER

Chemical name Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

Product number B137

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses An odourless mineral solvent for professional cleaning of fine fabrics which cannot be wet

cleaned. Fine Fabric Solvent Cleaner is intended only for use by hand cleaning application

according to label directions.

Uses advised against Do not heat solvent or use in water or solvent spray extraction machines or with vacuum

extraction. Do not use for curtain cleaning.

1.3. Details of the supplier of the safety data sheet

Supplier www.prochem.co.uk

Prochem Europe Ltd Oakcroft Road Chessington Surrey KT9 1RH

Telephone: 020 8974 1515 Fax: 020 8974 1511 sales@prochem.co.uk

1.4. Emergency telephone number

Emergency telephone 020 8974 1515 (office hours 8am to 5pm Monday to Friday) Emergency Action: In the event of

a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department, who may seek advice from the UK National Poisons Information Service, where our full product details are held. For Ireland contact the NPIC: 01 837 9964 or

01 809 2566.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 4 - H413

FINE FABRIC SOLVENT CLEANER

Human health Splashes in the eyes may cause redness and irritation. Prolonged skin contact may cause

redness, irritation and dry skin. Spray mists irritate the respiratory system, and cause coughing and difficulties in breathing. In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical

pneumonitis.

Environmental May cause long lasting harmful effects to aquatic life.

Physicochemical Flammable/combustible materials. The product may form explosive vapours/air mixtures even

at normal room temperatures.

2.2. Label elements

Pictogram





Signal word Danger

Hazard statements H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapour/ spray. P284 Wear respiratory protection.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents / container in accordance with local / regional / national /

international regulations.

Supplemental label

information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

Detergent labelling ≥ 30% aliphatic hydrocarbons

2.3. Other hazards

See section 8 for details of exposure limits. This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

FINE FABRIC SOLVENT CLEANER

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

60-100%

CAS number: 64741-65-7 EC number: 918-167-1 REACH registration number: 01-

2119472146-39-0001

Classification

Flam. Liq. 3 - H226 Asp. Tox. 1 - H304 Aquatic Chronic 4 - H413

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Keep the affected person warm and at rest. Get prompt medical attention. Keep affected

person under observation. Effects may be delayed. If in doubt, get medical attention promptly.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person under observation. Get medical attention if symptoms are severe or persist. Show this Safety

Data Sheet to the medical personnel.

Ingestion Get medical attention immediately. Keep affected person under observation. Do not induce

vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may

cause chemical pneumonitis. Show this Safety Data Sheet to the medical personnel.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing

immediately and wash skin with soap and water. Get medical attention if symptoms are

severe or persist.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes and get medical attention.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

soon as possible.

Inhalation Vapours/aerosol spray may irritate the respiratory system. In high concentrations, vapours are

anaesthetic and may cause headache, fatigue, dizziness and central nervous system effects. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death. Prolonged or

repeated exposure may cause the following adverse effects: Dizziness. Drowsiness.

Ingestion Gastrointestinal symptoms, including upset stomach. Diarrhoea. Nausea, vomiting. Entry into

the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin contact Skin irritation. Prolonged or repeated contact with skin may cause irritation, redness and

dermatitis.

Eye contact Vapour or spray in the eyes may cause irritation and smarting. Irritation, burning,

lachrymation, blurred vision after liquid splash.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctorNo specific recommendations.

Specific treatments No specific chemical antidote is known to be required after exposure to this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Flammable liquid and vapour. Containers can burst violently or explode when heated, due to

excessive pressure build-up. Solvent vapours may form explosive mixtures with air. May ignite

at high temperature.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon. Acrid smoke or fumes.

5.3. Advice for firefighters

Protective actions during firefighting

Move containers from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents. Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid inhalation of vapours and contact with skin and eyes. Eliminate all sources of ignition. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Take precautionary measures against static discharges. In case of spills, beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions

Environmental Manager must be informed of all major spillages. Do not discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Stop leak if possible without risk. DO NOT touch spilled material! Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Avoid the spillage or runoff entering drains, sewers or watercourses. Take care as floors and other surfaces may become slippery. Contain spillage with sand, earth or other suitable non-combustible material. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Dispose of contents/container in accordance with national regulations. Do not allow material to enter confined spaces, due to the risk of explosion.

6.4. Reference to other sections

Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours and spray/mists. Avoid release to the environment. Do not use in confined spaces without adequate ventilation and/or respirator. Use explosion-proof electrical, ventilating and lighting equipment. Eliminate all sources of ignition. Take precautionary measures against static discharges. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Do not mist or aerosolize spray.

Advice on general occupational hygiene

Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Clean equipment and the work area every day. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a well-ventilated place. Bund storage facilities to prevent soil and water pollution in the event of spillage. Keep away from food, drink and animal feeding stuffs. Only store in

correctly labelled containers.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C11-C12, isoalkanes, <2% aromatics

Long-term exposure limit (8-hour TWA): SUP 150 ppm 1000 mg/m³ SUP = Supplier's recommendation.

Ingredient comments

SUP = Supplier's recommendation.

8.2. Exposure controls

Protective equipment











Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours. Use explosion-proof electrical, ventilating and lighting equipment. Wear suitable respiratory protection. This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

Wear approved safety goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Solvent resistant nitrile gloves are recommended. To protect hands from chemicals, gloves should comply with European Standard EN374. Protective gloves should be inspected for wear before use and replaced regularly in accordance with the manufacturers specifications.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

FINE FABRIC SOLVENT CLEANER

Hygiene measures Do not eat, drink or smoke when using this product. Wash at the end of each work shift and

before eating, smoking and using the toilet. Remove contaminated clothing and protective equipment before entering eating areas. Wash contaminated clothing before reuse.

Respiratory protection Wear suitable respiratory protection. Wear a respirator fitted with the following cartridge:

Organic vapour filter. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Gas and combination filter cartridges should comply with European Standard EN14387. Change filter cartridge on respirator daily. Check that the respirator fits tightly and the filter is changed regularly. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure

Keep container tightly sealed when not in use.

controls

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid. Solvent.

Colour Colourless.

Odour Characteristic. Hydrocarbons.

Odour threshold Not determined.

pH Not applicable.

Melting point Not determined.

Initial boiling point and range 187 - 213°C @ 760 mm Hg

Flash point 60°C CC (Closed cup).

Evaporation rate Not determined.

Upper/lower flammability or

explosive limits

: 0.6

Other flammability Flammable/combustible materials.

Vapour pressure Not determined.

Vapour density 4.5

Relative density 0.761 @ 20°C

Solubility(ies) Insoluble in water. Soluble in the following materials: Hydrocarbons.

Partition coefficient Not determined.

Auto-ignition temperature Not determined.

Decomposition Temperature Not determined.

Viscosity Not determined.

Explosive properties Not determined.

Oxidising properties Not applicable.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

FINE FABRIC SOLVENT CLEANER

Reactivity The following materials may react with the product: Strong oxidising agents.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

The following materials may react with the product: Strong oxidising agents.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or

direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon. Acrid smoke or fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Ingestion. May cause discomfort if swallowed. Gastrointestinal symptoms, including upset

stomach. Diarrhoea. Nausea, vomiting. Spray/mists may cause respiratory tract irritation. Vapours and spray/mists in high concentrations are narcotic. When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause malaise such as headache, dizziness and nausea. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high

Skin corrosion/irritation

Skin corrosion/irritation Prolonged or repeated contact with skin may cause irritation, redness and dermatitis., May

cause sensitisation or allergic reactions in sensitive individuals.

Serious eye damage/irritation

Serious eye damage/irritation Vapour or spray in the eyes may cause irritation and smarting. May cause discomfort.

concentrations, unconsciousness and death.

Skin sensitisation

Skin sensitisation None known.

Germ cell mutagenicity

Genotoxicity - in vivoNo effects expected based upon current data.

Carcinogenicity

Carcinogenicity No effects expected based upon current data.

Reproductive toxicity

Reproductive toxicity - fertility No effects expected based upon current data.

Aspiration hazard

Aspiration hazard Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent

health problems.

Medical symptoms Gastrointestinal symptoms, including upset stomach. Dry skin.

Medical considerations Skin disorders and allergies.

SECTION 12: Ecological Information

Ecotoxicity The product contains a substance which may cause long-term adverse effects in the aquatic

environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable. Oxidises rapidly by photochemical reactions in

air.

12.3. Bioaccumulative potential

Bioaccumulative potentialThe product contains potentially bioaccumulating substances.

Partition coefficient Not determined.

12.4. Mobility in soil

Mobility The product is immiscible with water and will spread on the water surface. Absorbs to soil and

has low mobility. Large volumes may penetrate soil and could contaminate groundwater.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. When handling waste, the

safety precautions applying to handling of the product should be considered.

Disposal methods Empty containers or liners may retain some product residues and hence be potentially

hazardous. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Confirm disposal procedures with environmental engineer and local regulations. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste via a licensed

waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1268 UN No. (IMDG) 1268

FINE FABRIC SOLVENT CLEANER

14.2. UN proper shipping name

Petroleum distillates, N.O.S.

14.3. Transport hazard class(es)

IMDG class 3

14.4. Packing group

ADR/RID packing group III

IMDG packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

No special storage precautions required. Supplied in accordance with "Limited Quantity" provisions.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as

amended).

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18

December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information Telephone 020 8974 1515

Revision date 03/05/2017

Revision 2

Supersedes date 18/05/2015

SDS number 20398

Please note: Where abbreviations have been used elsewhere the full text has been written below, for the

classification of the product please refer to section 2.

Hazard statements in full H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Signature Aaron Saunders

For additional information on safety, training and use of this product, contact the supplier. This product is intended for professional use only. The information given is intended to be of assistance to users but is without guarantee. Variations can occur in application and users are advised to conduct their own tests. Suggestions for use neither give nor imply any guarantee as to the intended use.